

In the Claims

Please amend Claims 1, 6, 7, 9 and 18-20 as follows. Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned "Version with markings to show changes made to the Claims."

Please add new Claims 21-25. Below is a list of all the now pending claims.

- A1
1. (Amended) A transmitter comprising:
a voltage-controlled oscillator having an operating frequency; and
an antenna, the antenna forming part of a tuned circuit coupled to the voltage-controlled oscillator, a resonance point of the tuned circuit being automatically tuned to the operating frequency of the voltage-controlled oscillator.
 2. The transmitter of Claim 1, wherein the voltage-controlled oscillator is coupled serially with a phase detector and a loop filter to form a phase-locked loop.
 3. The transmitter of Claim 2, wherein the phase detector is further coupled to a reference signal so that the operating frequency of the voltage controlled oscillator is related to the frequency of the reference signal.
 4. The transmitter of Claim 1, wherein a power amplifier is coupled between the voltage controlled oscillator and the antenna.
 5. The transmitter of Claim 4, wherein the gain of the power amplifier is controlled by a power controller.
 6. (Amended) The transmitter of Claim 5, wherein the power amplifier, the voltage-controlled oscillator, and the power controller are formed on a single integrated circuit.
 7. (Amended) The transmitter of Claim 2, wherein the phase-locked loop further includes a prescaler and a divide-by M circuit coupled between the voltage-controlled oscillator and the phase detector.

8. The transmitter of Claim 7, wherein the voltage controlled oscillator and the phase-locked loop are formed on a single integrated circuit.

A3
9. (Amended) The transmitter of Claim 1, wherein the tuned circuit includes a differential structure of varactor diodes for tuning the resonance point of the antenna to the frequency of the voltage-controlled oscillator.

10. The transmitter of Claim 9, wherein the varactor diodes include an array of capacitors that can be switched in and out of the tuned circuit.

11. The transmitter of Claim 9, wherein the differential structure of varactor diodes and the voltage-controlled oscillator are formed on a single integrated circuit.

12. The transmitter of Claim 9, further including a varactor Charge pump to provide a bias Charge for varactor diodes in the differential structure of varactor diodes.

13. The transmitter of Claim 12, wherein the differential structure of varactor diodes, the voltage-controlled oscillator, and the varactor charge pump are formed on a single integrated circuit.

14. The transmitter of Claim 2, further including a reference oscillator supplying a signal of a reference frequency to the phase detector, wherein the reference oscillator, the voltage controlled oscillator, and the phase-locked loop are formed on a single integrated circuit.

15. The transmitter of Claim 14, wherein the reference oscillator is of the Colpitts variety and is coupled to receive a signal from a timing device external to the single integrated circuit.

16. The transmitter of Claim 1, further including a charge pump supplying a voltage to the voltage-controlled oscillator, wherein the charge pump and the voltage-controlled oscillator are formed on a single integrated circuit.

17. The transmitter of Claim 1, further including a bandgap reference circuit generating reference voltages that are temperature and supply voltage stable, the bandgap reference circuit and the voltage-controlled oscillator formed on a single integrated circuit.

18. (Amended) The transmitter of Claim 1, further including a shutdown mode circuit coupled to the voltage-controlled oscillator, the shutdown mode circuit and the voltage-controlled oscillator being formed on a single integrated circuit.

19. (Amended) The transmitter of Claim 1, further including a data encoder coupled between a data input pad and the voltage-controlled oscillator, the data encoder and the voltage-controlled oscillator being formed on a single integrated circuit.

20. (Amended) A method of transmitting, comprising:
generating an oscillating frequency with an oscillator within a phase-locked-loop;
modulating the oscillating frequency to create a modulated signal;
coupling the modulated signal to an antenna, the antenna forming part of a resonant network with the oscillator; and
automatically tuning a resonant point of the resonant network to the oscillating frequency.

21. (New) A transmitter comprising:
a voltage-controlled oscillator having an operating frequency;
an antenna, the antenna forming part of a tuned circuit coupled to the voltage-controlled oscillator,
a differential structure of varactor diodes;
varactor/Charge pump to provide a bias Charge for varactor diodes in the differential structure of varactor diodes; and
a tuned circuit including the antenna and the differential structure of varactor diodes, wherein the differential structure of varactor diodes tunes the resonance point of the antenna to the frequency of the voltage-controlled oscillator.

22. (New) The transmitter of Claim 21, wherein the voltage-controlled oscillator is coupled serially with a phase detector and a loop filter to form a phase-locked loop.

23. (New) The transmitter of Claim 21, wherein the differential structure of varactor diodes, the voltage-controlled oscillator, and the varactor charge pump are formed on a single integrated circuit.

24. (New) The transmitter of Claim 21, wherein the varactor diodes include an array of capacitors that can be switched in and out of the tuned circuit.

25. (New) The transmitter of Claim 21, wherein the differential structure of varactor diodes and the voltage-controlled oscillator are formed on a single integrated circuit.

LAW OFFICES OF
SKJERVEN MORRILL LLP

25 METRO DRIVE
SUITE 700
SAN JOSE, CA 95110
(408) 453-9200
FAX (408) 453-7979